AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A method for efficient routing in a multiple hop wireless communication network characterized in that data packets are routed over transmission paths using the following steps:

providing link status information by acquiring link status quality between nodes in the network;

updating a routing element (101)-with said link status information; determining possible routes with essentially similar link quality status for said data packet; and

routing said data packet via the determined routes.

- (Original) The method according to claim 1 further comprising the step of combining said data packets at a destination node.
- (Currently Amended) The method according to any of above claimsclaim 1
 further comprising the step of replacing one of said data packets with parity bits
 for error detection and error correction purposes.
- (Currently Amended) The method according to any of above claims claim 1
 characterized in that said wireless link comprise the step of using a

AXELSSON ET AL. Appl. No. Unknown June 23, 2006

transmission system based on electromagnetic radiation with a frequency in the range of 100 kHz to 100 PHz.

- 5. (Original) The method according to claim 4 characterized in that said transmission system comprise the step of using a transmission system from one or several of the following radio standards: IEEE 802.11, IEEE 802.15, IEEE 802.16 HiperLAN, HomeRF, Bluetooth, IR, UWB, JTRS, 3G, GPRS, and EDGE.
- 6. (Currently Amended) A system for efficient routing in a communication network having a plurality of nodes, each node comprising

link status acquiring (3001) means for acquiring information about link status between neighboring nodes;

updating means (102) for updating routing means (101) with said link status information;

determination means (3002) using said link status information for determining possible routes for routing of a data packet; and routing means (101) for routing said data packet via said determined routes.

7. (Original) A system according to claim 6 wherein communication between said nodes is wireless.

- 8. (Original) A system according to claim 7 wherein the communication network is an ad hoc network.
- (Original) The system according to claim 6 comprising the step of replacing one of said data packets with parity bits for error detection and error correction purposes.
- 10. (Original) The system according to claim 7 characterized in that said wireless communication comprise a transmission system based on electromagnetic radiation with a frequency in the range of 100 kHz to 100 PHz.
- 11. (Original) The system according to claim 10 characterized in that said transmission system is one or several of the following radio standards: IEEE 802.11, IEEE 802.15, IEEE 802.16 HiperLAN, HomeRF, Bluetooth, IR, UWB, JTRS, 3G, GPRS, and EDGE.
- 12. (Currently Amended) A node (800)-in a communication network having a plurality of nodes, said node comprising

processing means (801)-for processing network control information; storing means (802)-for storing network control information; transmission means (805)-for transmitting data packets; link status acquiring means (3001)-for acquiring link information comprising link status and link quality between neighboring nodes;

determination means (3002) using acquired link information for determining at least two routes to a destination for routing of a data packet; and routing means for routing said data packets via said determined routes.

- 13. (Currently Amended) The node (800)-according to claim 12 wherein communication between nodes is wireless.
- 14. (Currently Amended) The node (800) according to claim 13 wherein said communication network is an ad hoc network.
- 15. (Currently Amended) The node (800) according to claim 12 comprising the step of replacing one of said data packets with parity bits for error detection and error correction purposes.
- 16. (Currently Amended) The node (800)-according to claim 12 characterized in that said wireless communication comprise a transmission system based on electromagnetic radiation with a frequency in the range of 100 kHz to 100 PHz.
- 17. (Currently Amended) The node (800)-according to claim 16 characterized in that said transmission system is one or several of the following radio standards: IEEE 802.11, IEEE 802.15, IEEE 802.16 HiperLAN, HomeRF, Bluetooth, IR, UWB, JTRS, 3G, GPRS, and EDGE.

- 18. (Currently Amended) A wireless communication network comprising a system according to any of claims claim 6 11, comprising one or several nodes according to any of claims 12–17.
- 19. (Currently Amended) A computer program in a node in a wireless communication network, the program comprising:
 - a first instruction set for acquiring link status information between nodes in the network;
 - a second instruction set for updating a routing element (101) with said link status information;
 - a third instruction set for determining possible routes with essentially similar link quality status; and
 - a fourth instruction set for routing a data packet via said determined routes.